

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings of the claims in the application:

Listing of Claims:

1. (Currently Amended) A pigment dispersant system comprising:
 water;
 a polymeric pigment dispersant, the dispersant not having a binder;
~~a primary-amine~~ ammonium hydroxide; and,
 a defoamer.
2. (Original) The system of claim 1, wherein the water is deionized water.
3. (Canceled)
4. (Currently Amended) The system of claim [[3]] 1, wherein the ~~primary-amine~~
ammonium hydroxide is aqua ammonia 26% ammonium hydroxide.
5. (Original) The system of claim 4, wherein the defoamer is isobutyl
 isobutyrate.
6. (Original) The system of claim 5, wherein the polymeric pigment dispersant
 is a hyperdispersant.
7. (Original) The system of claim 1, wherein the polymeric pigment dispersant
 is chosen from the group comprising: an approximately 90% active polymeric dispersant, an
 approximately 100% active polymeric dispersant, an approximately 50% active polymeric
 dispersant, and an approximately 40% active polymeric dispersant.

8. (Original) The system of claim 1, wherein the dispersant further comprises an active synergist agent.

9. (Original) A solvent-based pigment dispersant system, the system comprising:

- a hydrocarbon solvent;
- a polymeric pigment dispersant, the dispersant not having a binder; and,
- a solvent compatible amine.

10. (Previously Presented) A solvent-based pigment dispersant system, the system comprising:

- a solvent chosen from the group comprising: acetates, ketones, and aromatics;
- a polymeric pigment dispersant, the dispersant not having a binder; and,
- a solvent compatible amine.

11. (Previously Presented) The system of claim 10, wherein the solvent is n-butyl acetate.

12. (Original) The system of claim 9, wherein the polymeric pigment dispersant is chosen from the group comprising: an approximately 90% active polymeric dispersant, an approximately 100% active polymeric dispersant, an approximately 50% active polymeric dispersant, and an approximately 40% active polymeric dispersant.

13. (Original) The system of claim 12, wherein the solvent compatible amine is diethylamine.

14. (Original) The system of claim 13, wherein the system further comprises an active synergist agent.

15. (Original) A method for making a pigment dispersant system, the method comprising the steps of, in order:

mixing 55.982% by weight deionized water, 0.372% by weight isobutyl isobutyrate, and 2.896% by weight of a polymeric pigment dispersant, without a binder;

adding into a constant vortex 22.683% by weight of a low surface area carbon black and 17.376% by weight kaolin clay;

adding 0.691% by weight aqua ammonium 26% ammonium hydroxide;

mixing in a high-speed mixing system all of the above components; and,

rinsing with deionized water and ammonium hydroxide.

16. (Original) A method for making a pigment dispersant system, the method comprising the steps of:

mixing water, a defoamer, and a polymeric pigment dispersant, without a binder;

adding to a vortex carbon black and a rheology modifier;

adding a primary amine;

mixing in a high-speed mixing system all of the above components; and,

rinsing with water and a primary amine.

17. (Original) The method of claim 16, wherein the water is deionized water, the defoamer is isobutyl isobutyrate, and the polymeric pigment dispersant is chosen from the group comprising: an approximately 90% active polymeric dispersant, an approximately 100% active polymeric dispersant, an approximately 50% active polymeric dispersant, and an approximately 40% active polymeric dispersant.

18. (Original) The method of claim 17, wherein the carbon black is a low surface area carbon black and the rheology modifier is a pigmented kaolin clay.

19. (Canceled)

20. (Currently Amended) ~~The method of claim 19, wherein the primary amine is aqua ammonium 26% ammonium hydroxide.~~ A method for making a pigment dispersant system, the method comprising the steps of:

mixing water, a defoamer, and a polymeric pigment dispersant, without a binder;
adding to a vortex carbon black and a rheology modifier;
adding ammonium hydroxide;
mixing in a high-speed mixing system all of the above components; and,
rinsing with water and ammonium hydroxide.

21. (Currently Amended) The method of claim 18, wherein the water, defoamer, pigment dispersant, carbon black, kaolin clay, and ~~ammonium hydroxide~~ amine are added in synergistically effective amounts.

22. (Original) The method of claim 21, wherein mixing in a high-speed mixing system all of the above components further comprises the step of:

mixing in a tank and cowles blade high-speed mixing system all of the above components at between approximately 3500 to approximately 4000 rpm.

23. (Original) A method for pigment grinding, the method comprising the steps of:

making a pigment dispersant system, the system being made by a method comprising:
 mixing water, a defoamer, and a polymeric pigment dispersant, without a binder;
 adding to a vortex carbon black and a rheology modifier;
 adding a primary amine;
 mixing in a high-speed mixing system all of the above components; and,
 rinsing with water and ammonium hydroxide; and,
 mixing a pigment with the pigment dispersant system, the pigment and pigment dispersant system being mixed in a high-speed mixer.

24. (Original) The method of claim 23, wherein mixing a pigment with the pigment dispersant system, the pigment and pigment dispersant system being mixed in a high-speed mixer further comprises the step of:

mixing a pigment with the pigment dispersant system, the pigment and pigment dispersant system being mixed in a high-speed mixer at a speed capable of overcoming the Van der Waals force.

25. (Original) The method of claim 24, wherein mixing a pigment with the pigment dispersant system, the pigment and pigment dispersant system being mixed in a high-speed mixer further comprises the step of:

mixing a pigment with the pigment dispersant system, the pigment and pigment dispersant system being mixed in a high-speed mixer at between approximately 1300 to approximately 2300 rpm.

26. (Currently Amended) The method of claim [[16]] 20, wherein the dispersant comprises molecules with ionic anchoring mechanisms, the mechanisms having hydrophilic and hydrophobic tails, wherein the molecules orientate themselves to exert the least amount of expended energy in bonding, wherein the molecules adsorb onto a exposed pigment surface area.

27. (Previously Presented) The method of claim 26, wherein the tail, with a greater square of distance that pigment particle to pigment particle, is capable of overcoming Van der Waals force, thereby breaking pigment agglomerates.

Please add new claims 28-31 as follows:

28. (New) The method of claim 20, wherein the ammonium hydroxide is aqua ammonium 26% ammonium hydroxide.

29. (New) A method for pigment grinding, the method comprising the steps of:
making a pigment dispersant system, the system being made by a method comprising:

mixing water, a defoamer, and a polymeric pigment dispersant, without a binder;
adding to a vortex carbon black and a rheology modifier;
adding ammonium hydroxide;
mixing in a high-speed mixing system all of the above components; and,
rinsing with water and ammonium hydroxide; and,
mixing a pigment with the pigment dispersant system, the pigment and pigment
dispersant system being mixed in a high-speed mixer.

30. (New) The method of claim 20, wherein the water, defoamer, pigment
dispersant, carbon black, kaolin clay, and ammonium hydroxide are added in synergistically
effective amounts.

31. (New) The method of claim 29, wherein the water, defoamer, pigment
dispersant, carbon black, kaolin clay, and ammonium hydroxide are added in synergistically
effective amounts.